



# Trimble T100

TABLET



Depend on it.

## KEY FEATURES

- ▶ **Fast and powerful processor**, for efficient data collection and data processing
- ▶ **Large 10.1-inch touchscreen**, sunlight readable and wet weather efficient with a high resolution display
- ▶ **Windows® 10**, brings the office to the field
- ▶ **Ergonomic design** that's comfortable and portable on long demanding days in the field
- ▶ **Expandable Trimble® Empower modules**, provide flexibility for user configurations

Learn more:  
[mcs.trimble.com/products-and-solutions/T100](https://mcs.trimble.com/products-and-solutions/T100)

# Trimble T100 TABLET

PRODUCT MODELS	T100 (WI-FI)	T100 (4G LTE)
WLAN (Wi-Fi)	Yes	Yes
4G Data	No	Yes
Memory storage (SSD)	512 GB	512 GB
GNSS Receiver	U-blox Neo-M8T	U-blox Neo-M8T

## STANDARD FEATURES

### System

- Intel® 8th Generation Core™ i5 Processor
- Intel HD Graphics 620
- 16 GB RAM<sup>1</sup>
- 512 GB Storage<sup>2</sup>
- 10.1" 800 nits 1920 x 1200 (16:10) LED-backlight screen with capacitive multi-touch
- Wacom Digitizer for EMR Pen Support
- 8 Megapixel with LED Flash rear camera
- Wi-Fi 802.11ac
- Bluetooth® v 5.1
- 4G LTE WWAN EM7565
- Internal battery 92 Wh non removable
- Integrated speaker and microphone
- IP65 Dust and Moisture Ingress Protection

### Operating System

- Microsoft® Windows® 10 Professional

### Communications

- Cellular: 4G LTE worldwide coverage, certified on Verizon and AT&T, data only
- Wi-Fi 802.11ac
- Bluetooth v 5.1
- USB 3.1 Type C x 2
- Supports USB C DisplayPort Alt Mode

### Standard Accessories

- EMR Stylus with replacement tips and removal tool
- AC-DC power adapter with power cord
- Screen protector
- USB A to USB C adapter

### Optional Accessories

- EMR Stylus and replacement tips and removal tool
- Handstrap
- Vehicle Power Supply
- Office stand
- Pole mount (Short and long versions)

## TECHNICAL SPECIFICATIONS

### Physical

- Size ..... 279 mm x 200 mm x 18.5 mm (11 in x 7.9 in x 0.7 in)
- Weight ..... 1.65 kg (3.6 lbs.)
- Processor ..... Intel® Core™ i5
- Memory ..... 16 GB SDRAM  
Storage: 512 GB SSD
- User Interface ..... Power button, directional pad, programmable function keys  
Power / Battery Status LED, On screen keyboard
- Battery ..... 92 Wh internal non removable
- Battery life ..... 10 hours @ 20 °C with GPS on
- Charging time ..... 1:15 to 50% 3 hours to 100%<sup>3</sup>

### Environmental

- Temperature  
Operating ..... -20 °C to +55 °C (-4 °F to 131 °F)<sup>4</sup>  
MIL-STD-810H 501.7 Procedure II
- Storage ..... -40 °C to +70 °C (-40 °F to 158 °F)  
MIL-STD-810H 501.76 Procedure I
- Thermal Shock ..... -20 °C and 60 °C non-operating  
MIL STD 810H Method 503.7 Procedure I-C
- Humidity ..... 0% - 95% non-condensing  
MIL STD 810H Method 507.6 Procedure I - Aggravated Cycle
- Water & dust proof ..... IEC 60629 Edition 2 - IP65
- Vibration / Shock resistance ..... MIL STD 810H Method 514.8 Procedure I  
- Random Vibration  
MIL STD 810H Method 514.8 Procedure II - Loose Cargo Transportation
- Drop ..... Tests include room temperature, -20 C, +60 C  
MIL STD 810H Method 516.8 Procedure IV - Transit Drop
- Chemical Exposure ..... Contamination by Fluids  
MIL STD 810H Method 504.3 Procedure II
- Non Operating Altitude ..... -30 °C and 40,000 Feet  
MIL STD 810H Method 500.6 Procedure I
- Operating Altitude ..... 5 °C and 30,000 Feet  
MIL STD 810H Method 500.6 Procedure II

### Input/Output

- Display ..... LED backlight scratch-resistant, auto rotate
- Size ..... 10.1" capacitive multi-touch with EMR
- Resolution ..... 1920 x 1200 px
- Brightness ..... 800 nits
- Audio ..... Built-in microphone and speaker
- I/O ..... USB 3.1 type c x 2  
Trimble EMPower Module Bays x 2
- AC / DC Adapter ..... AC 100~240 V, 50~60 Hz,  
DC 5 V, 9 V, 15 V, 20 V, 65 W  
USB C PD 65W
- Digital camera (rear facing) ..... 8MP with flash
- Sensors ..... E-Compass, Accelerometer, gyroscope, ambient light sensor, proximity sensor

### GNSS

- Internal antenna: 72 channels ..... Beidou, Galileo, GLONASS, GPS L1 C/A, QZSS, SBAS
- Integrated real-time ..... SBAS<sup>5</sup> (WAAS/EGNOS/MSAS/GAGAN)
- Dual constellation system ..... GPS/GLONASS or GPS/Beidou

### Accuracy Specifications (Horizontal RMS)<sup>6</sup>

- Real-time SBAS ..... < 4 m typical

1 1 GB = 1,000,000,000 bytes.  
 2 Total usable memory will be less depending upon actual system configuration.  
 3 Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other settings or preferences.  
 4 Tested under MIL-STD-810H method 501.6, Procedure II, and method 502.6, Procedure II. Battery capacity is reduced at lower temperatures or extremely high temperatures. Batteries should neither be charged at temperatures below 32 °F (0 °C) nor temperatures above 113 °F (+45 °C) to avoid impacting battery longevity and performance.  
 5 SBAS (Satellite Based Augmentation System), where available.  
 6 Horizontal Root Mean Squared accuracy. Requires reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception.

Caution: Do not expose bare skin to this product when handling this unit in extreme hot or cold environments. Do not charge batteries in extreme hot environments.

Specifications subject to change without notice



**BuildingPoint Pacific**  
 833 Montague Avenue  
 San Leandro, CA 94577  
 510.618.2550

11750 Sorrento Valley Road, Suite 140  
 San Diego, CA 92121  
 619.260.1552

21505 Bents Court NE  
 Aurora, OR 97002  
 503.280.1888



**NORTH AMERICA**  
 Trimble Inc.  
 10368 Westmoor Dr  
 Westminster, CO 80021  
 USA  
 1916.294.2000 Phone

